



### Description

Rack mountable 16-port 40 W PoE audio quality switch designed for use in Dante Networks. In addition to the 16 Ethernet ports, the STNet Switch II includes two SFP ports that can be adapted to fiber or high speed Ethernet connections. The two SFP ports can be turned into a high speed optical fiber ports or copper Ethernet ports with the addition of a Gigabit SFP transceiver module.

### Features

- 16 port high power 40 W PoE switch
- 2 SFP ports
- Compatible with any PoE or PoE+ devices
- Smart Switch technology
- Rack mount option 1-RU
- Designed for use on Dante Networks

### SoundTube®

13720 W. 109th St.  
 Lenexa, KS 66215  
 Phone: 913.663.5600  
 Fax: 913.663.3200  
 Toll Free: 855.663.5600  
[www.mseaudio.com](http://www.mseaudio.com)

All SoundTube speakers come with a 5-year limited warranty and 3-year warranty on all electronics.

### STNET SWITCH II PRODUCT SPECIFICATIONS

Power Requirements	110-240 VAC, 50/60 Hz; 8.5 Amps max consumption
10 M/100 M/1 G RJ45 Port	16
100 M/1 G SFP Port	2
Propriety (PoE+ 40 W)	Yes
IEEE802.af (PoE 15.4 W)	Yes
IEEE802.3at (PoE+ 30 W)	Yes
Available PoE Power	640 W
Operating Temperature	0°C - 40°C
Operating Humidity	10 - 90% RH
Storage Temperature	-20°C - 70°C
Storage Humidity	10 - 90% RH
AC Input	100 V - 240 V
Height	44 mm   1.73"
Width	442 mm   17.4"
Depth	211 mm   8.3"
Weight	3.5 kg   7.71 lbs
Certifications	RoHS, FCC, ETL-c/US, UL 60950-1 / 1EC 60950-1 / CE / EN 55032:2015 +AC:2016, Class A, CISPR 32:2015 +Cor 1:2016, Class A / AS/NZS CISPR 32:2015, Class A EN 61000-3-2:2014, Class A / EN 61000-3-3:2013 / EN 55024:2010, EN 55024:2010 +A1:2015 / 47 CFR FCC Part 15, Subpart B, Class A ICES-003:2016 Issue 6, Class A / ANSI C63.4:2014