

**SoundTube®**

13720 W. 109th St.  
 Lenexa, KS 66215  
 Phone: 913.663.5600  
 Fax: 913.663.3200  
 Toll Free: 855.663.5600  
[www.mseaudio.com](http://www.mseaudio.com)

All SoundTube speakers come with a 5-year limited warranty and 3-year warranty on all electronics.

**RF52-EZ PRODUCT SPECIFICATIONS**

Nominal Impedance	8 Ω
Impedance (Min)	7 Ω
Sensitivity dB @ 2.83 V / 1 M	88 dB
Sensitivity dB @ 1 W / 1 M (2)	88 dB
Frequency Response (±3 dB)	80 Hz - 20 kHz
Frequency Response (±10 dB)	58 Hz - 22 kHz
Max. Program Power	60 W
Max. Continuous Power RMS	30 W
Max. Power SPL @ 1 M	103 dB
Tap Selector	Wire leads with transformer bypass
70.7 V Transformer Taps	10 W, 5 W, 2.5 W, 1.3 W
100 V Transformer Taps (dB)	10 W, 5 W, 2.5 W
25 V Transformer Taps (dB)	N/A
Transformer Options	70.7 / 100 V option with an 8 Ω direct
Transducer: Low-Frequency Driver	5.25" polypropylene cone w/ butyl rubber surround
Transducer: High-Frequency Driver	0.75" poly carb tweeter
Network Type: Low Pass	6 dB per octave, 1st order
Network Type: High Pass	6 dB per octave, 1st order
Colors	White
Connections	Wire leads
Height	133 mm   5.5"
Diameter	197 mm   7.75"
Cutout Diameter	159 mm   6.25"
Mounting Depth	177 mm   4.625"
Weight	1.4 kg   3.1 lbs
Shipping Weight	1.8 kg   4 lbs
Packaging	One per box
Certifications	CCC, CE