



Round in-wall with the greatest visual discretion (FRAMELESS only 5 mm thickness), 2 ways, for in-ceiling loudspeaker.

### Produkt Blatt

Recessed circular shape speaker (FRAMELESS only 5 mm thickness), 100 V, 12-6-3 W, EN 54-24 certified.

ABS V0 structure and micro drilled grid for speaker protection, with a 6.5" coaxial 2-way speaker, linear audio transformer for connection to 100 V constant voltage lines, thermal fuse protection of the line in case of over-heating, ceramic type double terminals for separate connections.

Diameter of hole for flush mounting: 165mm.

Dimensions: Ø190.5 x built-in depth 102 mm.

Weight: 1 kg.

Color: White (B)

## Technische Merkmale

System	100V EN54-24
Leistung [Wrms]	12-6-3
Impedanz [ohm]	833-1666-3333 $\Omega$
Frequenzgang [Hz]	155÷18000
SPL [1W/1m]	91dB
SPL MAX	102dB
Abstrahlung [Grad]	180°
Gewicht [kg]	1 kg
Größe [mm]	Ø 190,5 mm, P95 mm

## Verfügbare Varianten

Keine Variante verfügbar

## Technische Zeichnung



## Grafik Frequenzgang



## Schaltschema

mod. : ECT4G6/12/24 - ECT4L12

